

# SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

## **[METHOD AND RELATED APPARATUS FOR CONTROLLING TRANSMISSION INTERFACE BETWEEN AN EXTERNAL DEVICE AND A COMPUTER SYSTEM]**

### Background of Invention

[0001] 1.Field of the Invention

[0002] The present invention relates to a method and a related apparatus for controlling transmission interface between an external device and a computer system, and more particularly, to a method and a related apparatus which embeds transmission interface data in a device configuration data of the external device.

[0003] 2.Description of the Prior Art

[0004] With advanced development of computer technology, the size of a computer system is gradually being reduced. The computer system is now used in a broad spectrum of fields. In order to expand additional functions of the computer system to meet requirements of different users, many kinds of external devices are invented under this situation. For example, an external hard disk drive or other portable data storage devices can increase the total data storage capacity of the computer system. An external optical drive and an external optical recordable drive can provide the computer system with an additional ability of accessing multimedia data recorded on compact disks and storing a great quantity of back-up data on the compact disk. In addition, an IC smart card and an external network card can individually provide other

functions to make the computer system become a more powerful tool for users.

[0005] If the external devices are designed to expand functions of the computer system, the external devices must be able to communicate with the computer system for transferring data. Please refer to Fig.1, which is a block diagram of a standard computer system 10 connected to prior art external devices 20A, 20B. The computer system 10 has a host 11 which comprises a central processing unit (CPU) 12A, a north bridge circuit 12B and a south bridge circuit 12C, a video graphics array (VGA) card 12D, a monitor 12E, a memory 12F, a soundcard 14A, a speaker 14D, an input device 14B, a hard disk drive 14C, and a connecting port 14E.

[0006] The computer system 10 usually has a plurality of external devices connected to the same host 11. The connecting port 14E, therefore, has a plurality of first connecting terminals. For clarity, there are only two first connecting terminals 16A, 16B shown in Fig.1. Each of the first connecting terminals 16A, 16B corresponds to an external device. As shown in Fig.1, the first external device 20A is connected to the host 11 through the first connecting terminal 16A, and the second external device 20B is connected to the host 11 through the second connecting terminal 16B. Taking the first external device 20A as an example, the structure and operation of the prior art external device is further described as follows. The first external device 20A has a second connecting terminal 18A corresponding to the first connecting terminal 16A. Furthermore, the first external device 20A has a transmission interface controller 22, a driver circuit 24B, a non-volatile memory 26B, and a kernel module 29. The transmission interface controller 22 has a bridge circuit 24A and a non-volatile memory 26A. The kernel module 29 is used for actually performing a predetermined function of the first external device 20A. For example, if the first external device 20A is an external hard disk drive, the kernel module 29 is the physical storage disk used for recording data. If the first external device 20A is an external optical drive, the kernel module 29 comprises a pick-up head and a motor for rotating the disk, etc. Similarly, if the first external device 20A is an external memory card, the kernel module 29 is a flash memory. The driver circuit 24B is used for controlling operation of the kernel module 29. The memory 26B electrically connected to the driver circuit 24B is used for storing device configuration data 28B of the first external device 20A, that is, the configuration information associated with the kernel module 29. For

example, if the first external device 20A is an optical drive, the device configuration data 28B comprises information about direct memory access (DMA). If the first external device 20A is an external hard disk drive, the device configuration data 28B comprises information about parameters such as capacity, cylinders, and sectors. The host 11 must obtain the device configuration data 28B to control external devices 16A, 16B through the transmission interface controller 22.

[0007]

In order to make different kinds of external devices suitable for the host 11, a plurality of connecting port standards are defined to meet different requirements. However, different specifications are not compatible with each other. The host 11 may adopt a universal serial bus (USB) specification (first format), but the external devices 16A, 16B may adopt another connecting port specification (second format). If the first external device 20A is an external hard disk drive, the first external device 20A requires commands compatible with an AT attachment (ATA) specification to control the driver circuit 24B. Similarly, if the first external device 20A is an external optical drive, the first external device 20A requires commands compatible with an ATA packet interface (ATAPI) specification to control the driver circuit 24B. Data compatible with the first format have a different structure and a different electronic character compared with the data compatible with the second format. The bridge circuit 24A, therefore, is necessary to convert data transmitted between the connecting port 14E and the driver circuit 24B. The bridge circuit 24A has a first port 25A for receiving and outputting data compatible with the first format and a second port 25B for receiving and outputting data compatible with the second format. The bridge circuit 24A can transform the data compatible with the first format (USB for example) into data compatible with the second format (ATA or ATAPI for example). That is, when the host 11 wants to control the first external device 20A, the host 11 will output commands compatible with the first format (signal S1 shown in Fig.1) through the connecting port 14E to the first external device 20A. The bridge circuit 24A of the first external device 20A will analyze the signal S1 to retrieve the original commands, and transmits the commands compatible with the second format (signal S2 shown in Fig.1) from the second port 25B to the driver circuit 24B. The driver circuit 24B then can control the kernel module 29 to perform some actions such as retrieving data according to the commands generated from the host 11. On the other hand, the data transferred from

the kernel module 29 and the driver circuit 24B to the host 11 will first be transmitted to the second port 25B of the bridge circuit 24A according to the second format, and the bridge circuit 24A then transforms the received data into data compatible with the first format. Finally, the data compatible with the first format are outputted from the first port 25A and are passed through the second connecting port 18A and the first connecting port 16A to arrive at the connecting port 14E. The host 11, therefore, can now conveniently exchange data with the external devices 20A, 20B through the transmission interface controller 22.

[0008] In addition to the above-mentioned signal format transformation, the transmission interface controller 22 further uses a non-volatile memory 26A to store the transmission interface data 28A. The transmission interface data 28A comprises unique identification data associated with the bridge circuit 24 such as a vendor identity code, a product identity code, manufacturer information, a serial number code, and so forth. As mentioned above, the many external devices nowadays can simultaneously attach to only one computer host, and the specific transmission interface data of each external device are used for identifying individual external devices so that the host can control those external devices through the connecting port. In other words, when the host wants to transmit a command to a specific external device, the host can assign unique transmission interface data associated with the desired external device at the same time so that the command will only be received by the external device compatible with the assigned transmission interface data.

[0009] To sum up, when the host 11 starts operating (power-on), the host 11 will search any external devices connected to the connecting port 14E. If there are external devices connected to the connecting port 14E (the first external devices 20A, 20B shown in Fig.1), the host 11 will ask every first external device 20A, 20B to hand over corresponding transmission interface data to the host 11. Taking the prior art first external device 20A as an example, when the bridge circuit 24A receives the request from the host 11, the bridge circuit 24A will retrieve the transmission interface data 28A from the memory 26A and transmit the transmission interface data 28A to the host 11. After the host 11 receives the transmission interface data of each external device, the host 11 can exchange data with the external devices by assigning specific

transmission interface data to select a corresponding external device. If the host 11 wants to control operation of the external devices, the host 11 will require the device configuration data of each external device. Taking the first external device 20A as an example again, when the bridge circuit 24A receives the request from the host 11, the bridge circuit 24A will transmit an "identify driver" command compatible with the second format (ATA or ATAPI) to the driver circuit 24B, and the driver circuit 24B will retrieve and transmit the device configuration data 28B to the bridge circuit 24A. Then, the bridge circuit 24A transmits the device configuration data 28B compatible with the first format to the host 11. After the host 11 gets the device configuration data 28B, the host 11 can control operation of the external device with adequate parameters and commands according to the device configuration data 28B.

[0010] The principal drawback mentioned above is that the driver circuit 24B and the transmission interface controller 22 respectively need memory 26B, 26A to store device configuration data 28B and the transmission interface data 28A. The device configuration data 28B are related to parameters required by the operation of the first external device 20A, and the transmission interface data 28A are related to control of the transmission interface between the host 11 and the first external device 20A. Both data must be stored in non-volatile memory. The prior art computer system uses two non-volatile memory 26A, 26B to store the device configuration data 28B and the transmission interface data 28A respectively. The non-volatile memory such as an electrically erasable programmable read-only memory (EEPROM) or a flash memory has a special structure compared with an ordinary logic circuit, and requires a special circuit design to work properly. Therefore, the production cost is high. In other words, the prior art transmission interface controller of the external device has a high production cost and a complicated circuit design.

## Summary of Invention

[0011] It is therefore a primary objective of the claimed invention to provide a method and a related apparatus for controlling transmission interface between an external device and a computer system with a simple circuit design to solve the above mentioned problem.

[0012] Briefly, the claimed invention provides a method for controlling a transmission

interface between a computer system and an external device to manage data transmission. The computer system comprises a host for controlling operation of the computer system, and a first connecting port for outputting and receiving a data compatible with a first format. The external device comprises a second connecting port for receiving the data compatible with the first format transmitted from the first connecting port and transmitting the data compatible with the first format to the first connecting port, a bridge circuit comprising a first port and a second port, a driver circuit for controlling operation of the external device according to the data compatible with the second format outputted from the second port of the bridge circuit, and a memory electrically connected to the driver circuit for storing transmission interface data. The first port is electrically connected to the second connecting port. The bridge circuit transforms the data compatible with the first format received by the first port into corresponding data compatible with a second format and outputs the data compatible with the second format through the second port. The bridge circuit transforms the data compatible with the second format received by the second port into the corresponding data compatible with the first format and outputs the data compatible with the first format through the first port. The host of the computer system transmits the data compatible with the first format to the bridge circuit of the external device according to a specification defined by the transmission interface data. The bridge circuit transmits a control signal compatible with the first format to the driver circuit for retrieving the transmission interface data stored in the memory, and the bridge circuit transmits the transmission interface data compatible with the first format to the host so that the host transmits data compatible with the first format to the bridge circuit according to the transmission interface data.

[0013]

It is an advantage of the claimed invention that the transmission interface data are embedded in the original reserved data space of the device configuration data. The device configuration data and the transmission interface data are both stored in the same non-volatile memory of the driver circuit. Therefore, there is no need to install an extra non-volatile memory in the transmission interface controller. When the host requests the transmission interface data, the transmission interface controller will issue an "identify driver" command compatible with the second format to the driver circuit. The transmission interface data are retrieved from the reserved data space of

the device configuration data. The claimed invention, briefly summarized, discloses a transmission interface controller with a simple circuit design and a low production cost.

[0014] These and other objectives of the claimed invention will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the preferred embodiment which is illustrated in the various figures and drawings.

## Brief Description of Drawings

[0015] Fig.1 is a block diagram of a standard computer system connected to prior art external devices.

[0016] Fig.2 is a block diagram of a computer system connected to external devices according to the present invention.

[0017] Fig.3 is a flow chart diagram illustrating the connection establishment between the host and the first external device.

## Detailed Description

[0018] Please refer to Fig.2, which is a block diagram of a computer system 30 connected to external devices 40A, 40B according to the present invention. The computer system 30 has a host 31 which comprises a central processing unit 32A, a north bridge circuit 32B, a south bridge circuit 32C, a VGA card 32D, a monitor 32E, a memory (a volatile data storage device) 32F, a soundcard 34A, a speaker 34D, an input device 34B, a hard disk drive (a non-volatile data storage device) 34C, and a connecting port 34E. The connecting port 34E (a USB connecting port for example) of the computer system 30 has a plurality of first connecting terminals 36A, 36B (only two connecting terminals are drawn in Fig.2 for clarity) corresponding to a first external device 40A and a second external device 40B respectively. Besides, signals compatible with the first format (USB signals for example) are transmitted from the connecting port 34E to the external devices 40A, 40B.

[0019] Taking the first external device 40A as an example, the general structure of the external device according to the present invention is further described as follows. The first external device 40A has a second connecting terminal 38A, a transmission

interface controller 42, a driver circuit 44B, a non-volatile memory 46 electrically connected to the driver circuit 44B, and a kernel module 49. Like the prior art first external device 20A, the kernel module 49 is used for performing the actual predetermined function of the first external device 40A, and the driver circuit 44B is used for controlling operation of the kernel module after receiving commands or signals compatible with the second format (ATA or ATAPI for example). In order to bridge the signals with different formats, the transmission interface controller 42 has a bridge circuit 44A. The bridge circuit 44A has a first port 45A and a second port 45B. The bridge circuit 44A can transform signals compatible with the first format into signals compatible with the second format. The signals or data compatible with the second format are received and outputted through the second port 45B. Similarly, the signals or data compatible with the first format are received and outputted through the first port 45A.

[0020]

Being analogous to the prior art first external device 20A, the host 31 needs the transmission interface data provided by the external devices to exchange data with the external devices correctly. In addition, the non-volatile memory 46 of the driver circuit 44B stores the device configuration data 48B to record parameters and information associated with operation of the kernel module 49. Generally speaking, the specification of the second format (ATA or ATAPI) specially defines a reserved data space allocated at the device configuration data so that the manufacturer of the external device can utilize the reserved data space to store additional information. The device configuration data 48B shown in Fig.2, for example, has a reserved data space 50. The prior art host does not need the information stored in the reserved data space when the external device is operating because the information stored in the reserved data space according to the prior art has nothing to do with the operation of the external device. But, the major difference between the prior art and the present invention is that the present invention uses the reserved data space 50 of the device configuration data 48B to store the essential transmission interface data 48A. Because the capacity of the reserved data space 50 is larger than the size of the transmission interface data 48A, the reserved data space 50 is suitable for storing the transmission interface data 48A undoubtedly. In order to check the transmission interface data 48A in the reserved data space 50, the reserved data space 50 further has a signature code



52. Because the transmission interface data 48A are embedded in the device configuration data 48B, the transmission interface controller 42, therefore, needs an extra non-volatile memory to keep the transmission interface data 48A no more.

[0021] As mentioned above, when the host 31 starts establishing connection with the first external device 40A, the host 31 must request the first external device 40A to give the transmission interface data. After receiving the request from the host 31, the bridge circuit 44A will issue an "identify driver" command compatible with the second format to the driver circuit 44B for retrieving the device configuration data 48B. When the bridge circuit 44A receives the device configuration data 48A read from the memory 46, the bridge circuit 44A can extract the corresponding transmission interface data 48A from the reserved data space 50 of the device configuration data 48A, and transmits the transmission interface data 48A to the host 31. The host 31 can correctly establish connection with the first external device 40A according to the transmission interface data 48A, and starts exchanging data with the first external device 40A now. In other words, the first external device 40A can perform its predetermined function to help the computer system 30. Please refer to Fig.3, which is a flow chart diagram illustrating the connection establishment between the host 31 and the first external device 40A. The related steps are described as follows.

[0022] Step 62: Start.

[0023] When the host 31 is going to establish connection with the first external device 40A, the procedures shown in Fig.3 are executed step by step. As mentioned above, when the host 31 is powered on, the host 31 will detect whether there are external devices connected to the host 31. If an external device is connected to the connecting port of the host 31, the host 31 will request the external device to give its transmission interface data. The request from the host 31 is compatible with the first format to be transmitted to the bridge circuit 44A of the first external device 40A through the first connecting terminal 36A and the second connecting terminal 38A.

[0024] Step 64:

[0025] After receiving the request from the host 31, the bridge circuit 44A issues an "ATA identify driver" command to the driver circuit 44B. The "ATA identify driver" command

has been defined by an ATA specification to drive the driver circuit 44B to read the device configuration data 48B from the memory 46. Then, the device configuration data 48B is transmitted to the bridge circuit 44A by the driver circuit 44B.

[0026] Step 66:

[0027] The bridge circuit 44A checks whether the driver circuit 44B has transmitted the device configuration data 48B to the bridge circuit 44A. If the bridge circuit 44A has received the device configuration data 48B, go to step 72; otherwise, go to step 68.

[0028] Step 68:

[0029] The bridge circuit 44A issues an "ATAPI identify driver" command to the driver circuit 44B. Concerning the preferred embodiment of the present invention, the first external device 40A is an external hard disk drive or an external optical drive. The driver circuit of the external hard disk drive needs the "ATA identify driver" command to read and pass the device configuration data. The driver circuit of the external optical drive needs the "ATAPI identify driver" command to read and pass the device configuration data. The driver 44B does not respond to the "ATA identify driver" command in step 66, which means that the driver circuit and the kernel module might belong to the external optical drive. Therefore, the bridge circuit 44A issues the "ATAPI identify driver" command to the driver circuit 44B again. If the same bridge circuit 44A is adopted by many external devices, the bridge circuit 44A can issue different formats of "identify driver" commands to request the driver circuit of each external device to give individual device configuration data. In the preferred embodiment, the bridge circuit 44A is designed to installed in the external hard disk drive or the external optical drive. The bridge circuit 44A at most issues two kinds of "identify driver" commands (steps 64, 68) to the driver circuit 44B.

[0030] Step 70:

[0031] If the bridge circuit 44A has received the device configuration data 48B, go to step 72; otherwise, go to step 78.

[0032] Step 72:

[0033] The bridge circuit 44A has received the device configuration data 48B from the

driver circuit 44B. Now, the bridge circuit 44A can check whether the signature code 52 in the device configuration data 48B is valid. As mentioned above, the predetermined signature code 52 is stored in the reserved data space 50 for determining whether the transmission interface data 48A is successfully embedded in the reserved data space 50. If the bridge circuit 44A finds that the retrieved signature code matches the predetermined signature code 52 in step 72, it is safe to proceed to the next step 74 because the transmission interface data 48A has been embedded in the reserved data space 50 correctly. If the bridge circuit 44A finds that the retrieved signature code does not match the predetermined signature code 52 in step 72, it means that the transmission interface data 48A has not been embedded in the reserved data space 50 correctly. Go to step 80.

[0034] Step 74:

[0035] The bridge circuit 44A extracts the transmission interface data 48A from the device configuration data 48A. In step 74, the bridge circuit 44A realizes that the transmission interface data 48A is recorded in the device configuration data 48B. After receiving the transmission interface data 48A, the host 31 can establish connection with the first external device 40A, and exchanges data with the first external device 40A.

[0036] Step 76:

[0037] End. After getting the transmission interface data 48A, the host 31 can control the first external device 40A to provide the host 31 with a specific function.

[0038] Step 78:

[0039] Execute a first exception handling mechanism. The bridge circuit 44A does not receive the transmission interface data from the driver circuit 44B. The bridge circuit 44A generates an error message to the host 31 so that the host 31 then can tell the user that the first external device 40A does not work normally or performs other remedial measures.

[0040] Step 80:

[0041] Execute a second exception handling mechanism. Though the bridge circuit 44A

has received the device configuration data 48B transmitted from the driver circuit 44B, the signature code 52 extracted from the device configuration data 48B shows that the transmission interface data 48A are not embedded in the reserved data space 50 of the device configuration data 48B. The bridge circuit 44A generates an error message to the host 31 for interrupting the whole procedure, or transmits a predetermined transmission interface data to the host 31 so that the host 31 can establish connection with the first external device 40A according to the predetermined transmission interface data.

[0042] The bridge circuit 44A according to the present invention not only can use an "identify driver" command to request the driver circuit 44B to retrieve the device configuration data 48B, but also can use a special defined command such as a "write" command to make the driver circuit 44B write the transmission interface data 48A into the memory 46. The host 31 must be able to execute a corresponding driver program such as a window-based driver utility to accomplish the objective of the "write" command. The user can use the driver program to transmit both the "write" command and the corresponding transmission interface data compatible with the first format to the bridge circuit 44A. The bridge circuit 44A then transmits the "write" command and the corresponding transmission interface data compatible with the second format to the driver circuit 44B so that the driver circuit 44B will embed the transmission interface data 48A and the corresponding signature code 52 in the reserved data space 50 of the device configuration data 48B. Therefore, the transmission interface data 48A embedded in the device configuration data 48B are capable of being updated at a user's request.

[0043] In contrast to the prior art transmission interface controller, the transmission interface controller according to the present invention uses the reserved data space of the device configuration data to store the transmission interface data. The transmission interface controller according to the present invention, therefore, does not require an extra non-volatile memory to store the transmission interface data. In other words, the external device with a simple circuit design certainly has a lower production cost. Furthermore, the reserved data space of the device configuration data has been defined by a standard specification already, and the transmission interface controller according to the present invention consequently can achieve the

objective of lowering the production cost and simplifying the circuit design without affecting original operation of the external device at all.

[0044] Those skilled in the art will readily observe that numerous modifications and alterations of the device may be made while retaining the teaching of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000